

HB11 LED High Bay Light



HB11

UFO High Bay Light



150-190 lm/W



IP65



IK08



Warranty



CCT Selectable




Power Selectable

HB11 LED High Bay Light

CCT & Power Selectable

A	B	C
120W	100W	80W
150W	120W	100W
200W	150W	100W
240W	200W	150W
300W	240W	200W

WW	NW	CW
3000K	4000K	5700K
4000K	5000K	6500K



Driver Supply

1. Input Voltage: AC100-277V, 50-60Hz
2. Dimming 0-10V / 0-10V with AUX DC 12V
3. UL/EU/AU Plug & Cable

Aluminum Housing

Die-casting technology by ADC12
excellent thermal management

High Brightness Lumileds LED Chips

1. CCT : 3000K/4000K/5000K/5700K/6500K
2. High Lumen Output: 150lm/W, 170lm/W and 190lm/W
3. Ra>70 / Ra>80 / Ra>90
4. Lifetime: 50,000H@L70

High Strength Polycarbonate Lens

1. Beam angle options : 60°/90°/110°
2. IK 08

Electrical Specification



Order Reference

ZGSM-HB11-150[A] A: >150lm/w B: >170lm/w C: >190lm/w D: CCT and Power Adjustable


Model No.	ZGSM-HB11-100 <input type="checkbox"/>	ZGSM-HB11-150 <input type="checkbox"/>	ZGSM-HB11-200 <input type="checkbox"/>	ZGSM-HB11-240 <input type="checkbox"/>	ZGSM-HB11-300 <input type="checkbox"/>
Power (10±%)	100W	150W	200W	240W	300W
Power Selectable	120W-100W-80W ADJ	150W-120W-100W ADJ	200W-150W-100W ADJ	240W-200W-150W ADJ	300W-240W-200W ADJ
Input Voltage	AC100-277V 50/60Hz				
Efficiency(5±%)	150lm/w / 170lm/w / 190lm/w				
Lumen (5±%)	15000lm / 17000lm / 19000lm	22500lm / 25500lm / 28500lm	30000lm / 34000lm / 38000lm	36000lm / 40800lm / 45600lm	45000lm / 51000lm / 57000lm
Power Factor	>0.95				
CRI	Ra>70 / Ra>80 / Ra>90				
CCT	3000K-6500K				
Beam Angle	60°/90°/110°				
IK Rating	IK08				
IP Rating	IP65				
Lifetime	50000Hrs@L70				
Product Size	Φ237*109mm	Φ260*111mm	Φ306*122mm	Φ362*127mm	Φ408*132mm
N.W	1.50kg	1.70kg	2.20kg	2.70kg	4.50kg
G.W	1.80kg	2.20kg	2.70kg	3.20kg	4.80kg
Packing Size	260*260*135mm	280*280*135mm	336*336*150mm	390*390*160mm	425*425*170mm

HB11 LED High Bay Light


Photometry



60°




90°




110°

Dimensions(mm)


01 ZGSM-HB11-100W □




02 ZGSM-HB11-150W □




03 ZGSM-HB11-200W □



04 ZGSM-HB11-240W □



05 ZGSM-HB11-300W □



Accessories Options



Alu Reflector



U Bracket



Emergency kits



Safety Steel Rope



Pipe Mount: 3/4 nut with M10



UL/EU/AU Plug & Cable